# SAFETY DATA SHEET

### 1. Identification

Product identifier 40-114 SILICONE 6% LEK

Other means of identification

Product code 1000019681
Recommended use Lubricant
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name IDEAL INDUSTRIES, CORP. (CANADA)

Address 33 FULLER ROAD

AJAX, ONTARIO L1S 2E1

Canada

**Telephone** General Assistance 1-800-527-9105

**E-mail** Not available.

Emergency phone number Emergency - US 1-866-836-8855

Emergency - Outside US 1-952-852-4646

Supplier Not available.

# 2. Hazard(s) identification

Physical hazardsFlammable aerosolsCategory 1Health hazardsSkin corrosion/irritationCategory 2Serious eye damage/eye irritationCategory 2

Carcinogenicity Category 2
Reproductive toxicity (fertility, the unborn Category 1B

child)

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Specific target organ toxicity, single exposure Category 3 narcotic effects

Specific target organ toxicity, repeated

exposure

#### Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Causes skin irritation. Causes serious eye irritation. May cause

respiratory irritation. May cause drowsiness or dizziness. Suspected of causing cancer. May damage fertility. May damage the unborn child. May cause damage to organs through prolonged

Category 2

or repeated exposure.

**Precautionary statement** 

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

Product name: 40-114 SILICONE 6% LEK SDS CANADA

Product #: 1000019681 Version #: 01 Issue date: 03-31-2017

IF ON SKIN: Wash with plenty of water. IF INHALED: Remove person to fresh air and keep Response

> comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off

contaminated clothing and wash it before reuse.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

**Environmental hazards** Hazardous to the aquatic environment, acute Category 3

hazard

Hazardous to the aquatic environment, Category 3

long-term hazard

Other hazards None known.

Supplemental information None.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	<u></u>
1-Bromopropane		106-94-5	69.09
1,2-Butylene Oxide		106-88-7	0.705
Other components below r	eportable levels		30.205

All concentrations are in percent by weight (kg) unless ingredient is a gas. Gas concentrations are in percent by volume (I).

## 4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get

medical advice/attention. Wash contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth. Ingestion

Most important

symptoms/effects, acute and

delayed

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special

treatment needed

**General information** 

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

#### 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Alcohol resistant foam. Powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not

breathe fumes.

General fire hazards Extremely flammable aerosol.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

#### 8. Exposure controls/personal protection

#### Occupational exposure limits

211	ACGIH	<b>Threshold</b>	Limit	Value
US.	ACGIR	inresnoia	LIIIIII	values

Components	Туре	Value
1-Bromopropane (CAS 106-94-5)	TWA	0.1 ppm
Canada. British Columbia OELs Safety Regulation 296/97, as am	• •	s for Chemical Substances, Occupational Health and
Components	Туре	Value
1-Bromopropane (CAS 106-94-5)	TWA	10 ppm
Canada. Manitoba OELs (Reg. 2	17/2006, The Workplace Safety	And Health Act)
Components	Туре	Value
1-Bromopropane (CAS 106-94-5)	TWA	0.1 ppm
Canada. Ontario OELs. (Control	of Exposure to Biological or C	hemical Agents)
Components	Туре	Value
1-Bromopropane (CAS 106-94-5)	TWA	10 ppm

No biological exposure limits noted for the ingredient(s).

Product name: 40-114 SILICONE 6% LEK

**Biological limit values** 

# Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

#### Individual protection measures, such as personal protective equipment

**Eye/face protection** Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

**Respiratory protection**Chemical respirator with organic vapor cartridge and full facepiece. **Thermal hazards**Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

# 9. Physical and chemical properties

**Appearance** 

Physical state Gas.
Form Aerosol.
Color Not available.
Odor Not available.
Odor threshold Not available.
PH Not available.
Melting point/freezing point Not available.
Initial boiling point and boiling Not available.

range

Flash point 600.8 °F (316.0 °C) estimated

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 14.03 psig @70F estimated

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

**Density** 1.29 g/cm3 estimated

Explosive properties Not explosive.

Heat of combustion 0.36 kJ/g estimated

Product #: 1000019681 Version #: 01 Issue date: 03-31-2017

Oxidizing properties Not oxidizing.

Percent volatile 95.5 % estimated

Specific gravity 1.287 estimated

# 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

**Conditions to avoid**Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

**Hazardous decomposition** 

products

Toxic gas.

# 11. Toxicological information

## Information on likely routes of exposure

**Inhalation** May cause damage to organs through prolonged or repeated exposure by inhalation. May cause

drowsiness and dizziness. Headache. Nausea, vomiting. May cause irritation to the respiratory

system.

**Skin contact** Causes skin irritation.

**Eye contact** Causes serious eye irritation.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause

respiratory irritation. Skin irritation. May cause redness and pain.

#### Information on toxicological effects

Acute toxicity Narcotic effects. May cause respiratory irritation.

Components	Species	Test Results
4.0 Destalana Ostida (040.4	100 00 7)	

1,2	-Buty	lene	Oxide	(CAS	106-88-7)	
-----	-------	------	-------	------	-----------	--

<u>Acute</u>
Dermal

LD50 Rabbit 1500 - 2950 mg/kg, 24 Hours

1.77 ml/kg, 24 Hours

Inhalation

Vapor

LC50 Rat > 6.3 mg/l

Oral

LD50 Rat 1 - 1.58 mg/kg

1100 µl/kg 1.3 ml/kg

1-Bromopropane (CAS 106-94-5)

<u>Acute</u>

Dermal

LD50 Rabbit >= 10 ml/kg, 24 Hours

Rat > 2000 mg/kg, 24 Hours

Inhalation

LC50 Rat 14374 ppm, 4 Hours

35 mg/m3, 4 Hours 25 - 35 mg/l, 6 Hours

Oral

LD50 Rabbit 540 mg/kg

Product name: 40-114 SILICONE 6% LEK

Components Species Test Results

Rat > 2000 mg/kg

\* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Serious eye damage/eye Causes skin irritation.

Causes serious eye irritation.

irritation

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

**Carcinogenicity** Suspected of causing cancer.

**ACGIH Carcinogens** 

1-Bromopropane (CAS 106-94-5)

A3 Confirmed animal carcinogen with unknown relevance to

humans.

Canada - Manitoba OELs: carcinogenicity

1-BROMOPROPANE (CAS 106-94-5) Confirmed animal carcinogen with unknown relevance to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

1,2-Butylene Oxide (CAS 106-88-7)

2B Possibly carcinogenic to humans.

**Reproductive toxicity** May damage fertility. May damage the unborn child.

Specific target organ toxicity -

single exposure

May cause respiratory irritation. May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

May cause damage to organs through prolonged or repeated exposure.

**Aspiration hazard** Not an aspiration hazard.

Chronic effects May cause damage to organs through prolonged or repeated exposure. Prolonged exposure may

cause chronic effects.

#### 12. Ecological information

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

Components		Species	Test Results	
1,2-Butylene Oxide (C	AS 106-88-7)			_
Aquatic				
Algae	IC50	Algae	500 mg/L, 72 Hours	
Crustacea	EC50	Daphnia	69.8 mg/L, 48 Hours	
Fish	LC50	Fish	160, 96 Hours	
1-Bromopropane (CAS	S 106-94-5)			
Aquatic				
Fish	LC50	Fathead minnow (Pimep	hales promelas) 67.3 mg/l, 96 hours	

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

**Bioaccumulative potential** 

Partition coefficient n-octanol / water (log Kow)

1-Bromopropane 2.1

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

Product name: 40-114 SILICONE 6% LEK SDS CANADA

# 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

# 14. Transport information

**TDG** 

UN1950 **UN** number

**UN** proper shipping name Transport hazard class(es) AEROSOLS, flammable

Class 2.1 Subsidiary risk

Packing group Not applicable.

**Environmental hazards** 

Special precautions for user Not available.

IATA

UN1950 **UN** number

**UN** proper shipping name

Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk Label(s) 2.1

**Packing group** Not applicable.

**Environmental hazards** No. **ERG Code** 101

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

**IMDG** 

UN1950 **UN** number **UN** proper shipping name **AEROSOLS** 

Transport hazard class(es)

Class 2.1 Subsidiary risk Label(s)

Not applicable. Packing group

**Environmental hazards** 

Marine pollutant No. F-D, S-U **EmS** 

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Not applicable. Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

Product name: 40-114 SILICONE 6% LEK SDS CANADA

# IATA; IMDG; TDG



# 15. Regulatory information

#### **Canadian regulations**

## **Controlled Drugs and Substances Act**

Not regulated.

#### Export Control List (CEPA 1999, Schedule 3)

Not listed

#### **Greenhouse Gases**

Not listed.

## **Precursor Control Regulations**

Not regulated.

#### International regulations

#### **Stockholm Convention**

Not applicable.

## **Rotterdam Convention**

Not applicable.

#### **Kyoto protocol**

Not applicable.

#### **Montreal Protocol**

Not applicable.

#### **Basel Convention**

Not applicable.

# **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

Toxic Substances Control Act (TSCA) Inventory

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other Information

**Issue date** 03-31-2017

Version # 01

United States & Puerto Rico

Product name: 40-114 SILICONE 6% LEK SDS CANADA

Yes

Disclaimer

We cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

**Revision information** 

Product and Company Identification: Alternate Trade Names

Product name: 40-114 SILICONE 6% LEK

SDS CANADA